

## SE 6000D

Electric Start Yanmar diesel engine with direct injection, high engine temperature shutdown, low oil pressure shutdown and low fuel shutdown / Acoustic cabinet with large access hood for ease of maintenance / High efficiency exhaust silencer / Industrial duty two wheeled trolley frame complete with lifting eye and front protective bull bar / Brushless maintenance free Markon NAC alternator with exceptional component design quality / Dual voltage output complete with overload protection / Centre tapped to earth (CTE 115V) / Integral 24lt fuel tank giving up to 17 hours running at 75% load / Compact design and lightweight in its class

SE 6000D 6.0kVA / 4.8KW / YANMAR L100

Standard Features : Electric Start Yanmar diesel engine with direct injection, high engine temperature shutdown, low oil pressure shutdown and low fuel shutdown / Acoustic cabinet with large access hood for ease of maintenance / High efficiency exhaust silencer / Industrial duty two wheeled trolley frame complete with lifting eye and front protective bull bar / Brushless maintenance free Markon NAC alternator with exceptional component design quality / Dual voltage output complete with overload protection / Centre tapped to earth (CTE 115V) / Integral 24lt fuel tank giving up to 17 hours running at 75% load / Compact design and lightweight in its class at only 160Kg

### **Specifications**

**OUTPUT:**

6.0kVA / 4.8KW

**SOCKETS:**

BS4343 industrial sockets -

2 x 115V 16A sockets

1x 115V 32A sockets

2 x 230V 16A sockets

**ENGINE:**

YANMAR L100

**HP/CYLINDERS:**

10/1

**FUEL TANK:**

24.0 litres

**RUN TIME:**

17 hours @ 75% Load

**NOISE LEVEL:**

71dB (A) @ 7 metres. 96LWA

**SIZE:**

L1220x W710 x H910mm

**WEIGHT:**

160kg